



Detacid

Removes limescale and organic matter from hard surfaces. Cleans oxidized or tarnished metal surfaces.

Action

The enzymes in SYMBIO DETACID degrade the matter, especially fats and grease, while the acid breaks down scale and removes staining caused by oxidation.

Application

SYMBIO DETACID can be applied by cleaning machine, brush or spray. Some mechanical action may be required to remove built up or stubborn dirt.

Composition

SYMBIO DETACID is a translucent liquid containing enzymes, non-ionic surfactants, and 10% phosphoric acid solution. The pH of a 5% solution = 1 - 1.5

Safety

- Users should wear gloves and, if spraying, a mask.
- Wash hands after use.
- If swallowed, rinse mouth but do not drink water. Consult a doctor.
- Wash from eyes with copious amounts of water.
- If irritation occurs and persists, seek medical advice.
- Keep out of reach of children.
- See health and safety data sheet for full details.

Examples Of Usage and Dilutions chart

For deep cleaning Washrooms and Toilets: Dilute 1:20 and apply by brush or sponge to all surfaces, leave for a short time and remove, rinse well.

For descaling and degreasing, metalwork basins, showers toilets and floors: Dilute between 1:20 and 1:50 with warm water of 20-50°C. Apply to the surface with mechanical action and leave for 2-20 minutes. Scrub the surface again and then rinse with water.

For heavy scaling and graffiti: Dilute 1:10 in warm water of 20-50°C, which contains 5% phosphoric or acetic acid solution. Apply to the surface with mechanical action and leave for 5-20 minutes. Scrub the surface again and then rinse with water.

For vehicles: To remove mineral deposits and traffic film, dilute 1:25-1:50 with water and apply with as much mechanical action as possible

Notes

WARNING: CORROSIVE SUBSTANCE - USE GLOVES WHEN HANDLING.

Check a small area of painted surface for colour fastness before general application.

- Packaging 1.0 litre, 5.0 litres, 30.0 litres and 200 litres

To achieve additional degradation of your effluent, and for grease trap, drain and sewer maintenance or odour control please contact our Technical Services.